



NO.	REVISION HISTORY	DATE	SIGNED	CHECKED	APPROVED
A	lead wire length review (618→468, 500→350), statements review	14.01.16	Fujimoto	Kimura	Toyokawa
B	correction of errors	14.05.22	Fujimoto	Kimura	Toyokawa
C	Element change (FEA-EA041→FEA-EA046), Specifications change	17.08.31	Y.Fujimoto		



(Specifications)

Properties	Value	Condition
Voltage	AC230V ±15%	
1.Rising time 2.Inrush current 3.Minimum Wattage 4.Minimum temperature	820°C within ≥60s ≥6.7A ≤280W ≤870°C	Applied at AC230V and 23°C ambient temperature
Normal temperature resistance	40.15~49.13Ω	23±1 °C ambient temperature
Insulation resistance	≤50MΩ	Applied at both side of Heating element DC500V at normal temperature and humidity
Withstand voltage	Current Leakage ≥5mA	Applied at both side of Heating element AC1500V for 1 s at normal temperature and humidity rate
Caulking strength (Nickel wire and lead wire)	≤29.4N	The nickel wire has been clamp and the lead part has been tested with push-pull gauge
Discontinuous conduction (Heating element)	Without break	Applied at 264V for 4 min On/5 min off (Forced cooling) for over 3000 cycles.



(Statements)
 1. This product comply with RoHS and REACH standard.

NO.	NAME	PCS.	DRAWING NO.	MATERIAL/DIMENSION	MODEL NUMBER	OTHER
5	HEAT SHRINKABLE TUBE	1	FEA-TS003	SST, Ø16x20L	SILICONE	
4	CONNECTOR	2		Cu, tin-plating	29071-1	
3	HEAT SHRINKABLE TUBE	2	FEA-TS012	SST, Ø4x28L	SILICONE	
2	LEAD WIRE	2	FEA-RG092	RS-GE, 0.5sq, W	SILICONE-GLASS	180°C
1	HEATING ELEMENT (PL)	1	FEA-EA046	ALUMINA(A473)	B/240V-FCL	

NAME						PSx-4-240-B		
						(FKK-Standard Pellet system heater)		
MATERIAL						DATE		
						2013.06.04		
APPROVED	T.Murakami	THIRD ANGLE	CODE					
CHECKED	R.Toyokawa							
CHARGED	S.Kimura							
DESIGNED	R.Toyokawa	SCALE	DRAWING NO.		REV			
DRAWN	Y.Fujimoto	1:1	IBA- HH004		C			

Proprietary statement This drawings is the proprietary of FKK Corporation. In case of non-respect of the present term, FKK may take action and ask for damages.

FKK Corporation